

# 6 AND 12 VOLT COMMERCIAL STARTING BATTERIES



- + Framed, centerline calcium constructed plates
- + Premium POSI-WRAP™ envelope separators
- + Maintenance-free flush top with manifold vent design
- + Heat-sealed case and cover design
- + Proven CCA and RC in-the-field performance
- + Extended battery service life



Product Code	Volts	Electrical Capacity			Physical Specifications			
		CCA	CA	RC @25 Amps	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
CR1640	6	640	810	130	231	176	222	14
CR24550	12	550	690	85	260	171	229	18
CR24675	12	675	850	105	260	171	229	19
CR24F675	12	675	850	105	272	171	229	19
CR24800	12	800	1000	120	260	171	229	21
CR30H775	12	775	970	170	328	171	235	27
CR31A775	12	775	970	170	329	171	240	26
CR31S775	12	775	970	170	329	171	240	26
CR31ASD775	12	775	970	180	329	171	240	27
CR31SSD775	12	775	970	180	329	171	240	27
CR4D1000	12	1000	1250	300	524	219	254	45
CR8D1100	12	1100	1375	340	524	278	254	53
CR8D1475	12	1475	1845	430	524	278	254	60

# HEAVY DUTY MARINE STARTING BATTERIES

- + The industry heavyweight, featuring the most active material and delivering unsurpassed CA and RC power and in-service durability
- + Proven CCA and RC in-the-field performance
- + Quality manufacturing processes



Product Code	Volts	Cranking Performance	Reserve Capacity		Physical Specifications			
		MCA	CCA	RC @25 Amps	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
CRM500	12	550	440	65	283	171	238	17
CRM600	12	625	500	75	283	171	238	18
CRM800	12	850	675	105	283	171	238	20
CRM1000	12	1000	800	120	283	171	238	21
CRM1000X	12	1000	800	125	334	171	238	23